



1510 Protector Carry-On Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Maximum airline carry on size*
- **Strong polyurethane wheels with stainless steel bearings**
- **Watertight, crushproof, and dustproof**
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded top and side handles
- Easy open Double Throw latches
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Retractable extension handle
- Stainless steel hardware and padlock protectors
- Peli's legendary lifetime guarantee**
- * Check with your airline for exact measurement requirements.
- * Where applicable by law



CONFIGURATIONS



1510
Standard

1514
With Padded Dividers

1510NF
No Foam

1510TP
With TrekPak Divider System

1510WF
With Foam

1510TPF
TrekPak / Foam Hybrid

DIMENSIONS

Interior (L×W×D)	19.75 x 11.00" x 7.60 (50.2 x 27.9 x 19.3 cm)
Exterior (L×W×D)	22.00 x 13.81" x 9.00 (55.9 x 35.1 x 22.9 cm)
Lid Depth	1.79" (4.5 cm)
Bottom Depth	5.79" (14.7 cm)
Total Depth	7.58" (19.3 cm)
Int Volume	0.96 ft ³ (0.027 m ³)
Padlock Hole Diameter	5/16" (12.7 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS

Purge Vent

3 Micron Hydrophobic Non-Woven

COLOURS

■ Black ■ Desert Tan ■ Yellow

WEIGHT

Weight With Foam 13.60 lbs (6.2 kg)
Weight Empty 11.99 lbs (5.4 kg)
Buoyancy 64.15 lbs (29.1 kg)
**Weight With TrekPak /
Foam Hybrid** 14.94 lbs (6.8 kg)
Master Pack Weight 32.43 lbs (14.7 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C)
Maximum Temperature 210°F (98.9 °C)

CERTIFICATIONS

IP67
Def Stan 81-41
STANAG 4280

FOAM PROPERTIES

Layer 1 (Lid) 1.81" Convolute
Layer 2 (Base) 0.50" Pad
Layer 3 (Base) 2.63" Pick N Pluck
Layer 4 (Base) 2.63" Pick N Pluck

OTHER

Wheels 2
Extendable Handle yes
Master Pack 2
Nameplate yes
Reduced Area yes
Military yes

ACCESSORIES



1511
4 pc. Replacement Foam Set



1513
Replacement O-ring



1515
Padded Divider Set



1519
Lid Organizer



1510EUTP
TrekPak Case Divider Kit



1507
Quick Mounts - set of 4



1506TSA
TSA Lock



1500D
Desiccant Silica Gel
