

# 1730

## Protector

Transport Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- · Watertight, crushproof, and dustproof
- 5-piece foam set
- Automatic Pressure Equalization Valve balances interior pressure, keeps water out
- Easy open Double Throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Optional Humidity gauge changes color above 40%
- Optional Manual Pressure Equalization Valve
- Stainless steel hardware and padlock protectors



#### **CONFIGURATIONS**







1730NF No Foam



1730WF With Foam

#### **DIMENSIONS**

Interior (L×W×D) 34.00 x 24.00" x 12.50 (86.4 x 61 x 31.8 cm) Exterior (L×W×D) 37.50 x 27.13" x 14.37 (95.3 x 68.9 x 36.5 cm)

 Lid Depth
 2.50" (6.4 cm)

 Bottom Depth
 10.00" (25.4 cm)

 Total Depth
 12.5" (31.8 cm)

 Int Volume
 5.9 ft³ (0.167 m³)

 Padlock Hole Diameter
 5/16" (12.7 cm)

#### **MATERIALS**

**Body** Polypropylene

Latch ABS
O-Ring Polymer
Pins Stainless Steel
Foam 1.3 lb Polyurethane

Purge Body ABS

**Purge Vent** 3 Micron Hydrophobic Non-Woven

# **COLOURS**



## WEIGHT

 Weight With Foam
 38.00 lbs (17.2 kg)

 Weight Empty
 30.00 lbs (13.6 kg)

 Buoyancy
 416.00 lbs (188.7 kg)

 Master Pack Weight
 43.00 lbs (19.5 kg)

# **TEMPERATURE**

**Minimum Temperature** -40°F (-40 °C) **Maximum Temperature** 210°F (98.9 °C)

## **CERTIFICATIONS**

IP67

#### FOAM PROPERTIES

 Layer 1 (Lid)
 2.50" Convolute

 Layer 2 (Base)
 1.00" Pad

 Layer 3 (Base)
 2.94" Pick N Pluck


Layer 4 (Base) 2.94" Pick N Pluck Layer 5 (Base) 2.94" Pick N Pluck

## **OTHER**

Wheels2Master Pack1Nameplateyes

# **ACCESSORIES**







**1733** Replacement O-ring



**1506TSA** TSA Lock



**1500D** Desiccant Silica Gel