

Product specification sheet

Product title

3SKB-R906U24 SKB 6U Industrial Shock Mount Rack







Description

3SKB 24? Shock Racks will keep your equipment safe and working while you travel in harsh conditions where your case and devices may be exposed to rough weather, mistreatment, and abuse. These cases are roto-molded to provide excellent strength, durability, and protection. The hinged doors are user friendly with a gasket seal that makes the case water resistant and keeps your gear dry! The supplied caster kit ensures that transport has never been easier?no more heavy lifting and carrying. For efficient and secure transport, these Shock Racks stack perfectly even with the casters mounted! These 24? deep rack models are suitable for IT equipment such as routers, switches, storage and communication devices. Additional applications are in military, security, outdoor, broadcast and many more markets.

Features

- · Patent pending compound hinged doors ensure easy opening & closing
- · Gasket-sealed doors keep your devices dry & safe
- · Smart design provides enough space for air circulation & heat dissipation
- · Threaded steel rails offer enhanced durability
- · Rear rack rails for even more secure fixing of your equipment
- · No more heavy lifting?4? castor kit standard included
- · Cases are shock & water resistant for added protection
- · A built-in pressure relief valve helps to maintain an ideal environment at any altitude
- Cases stack superbly with the wheels on or off for efficient & secure transport
- · Stainless steel recessed latches provide extra durability

Specifications

Interior Length	61.0 cm	24.1 inch
Interior Width	48.3 cm	19.1 inch
Interior Height	26.7 cm	10.6 inch
Base Depth	11.4 cm	4.5 inch
Lid Depth	11.4 cm	4.5 inch
Exterior Length	91.4 cm	36.0 inch
Exterior Width	67.3 cm	26.5 inch
Exterior Height	49.5 cm	19.5 inch
Carton Length	93.0 cm	36.7 inch
Carton Width	67.5 cm	26.6 inch
Carton Depth	51.0 cm	20.1 inch
Rack Depth	61.0 cm	24.1 inch
Depth Front Rail to Rail	61.0 cm	24.1 inch
 Depth Front Rail to Back Lid 	72.4 cm	28.6 inch
Shipping Weight	37.0 kg	81.6 lb
Product Weight	33.8 kg	74.5 lb
ATA Rated		
Rack Units: 6		