

## Mod. 7635HL.B E


7635HL- EXPLORER CASES, COPOLYMER POLYPROPYLENE ULTRALIGHT WATERPROOF CASE

# HL SERIES

Large cases IP67 certified. Two man lift side handles and retractable handle. Self-oiling free running wheels. Four colors available and two internal standard configurations.




METRIC MM-KG-C°



| INTERNAL DIMENSIONS |        | EXTERNAL DIMENSIONS |        | OTHER DATA              |                     |
|---------------------|--------|---------------------|--------|-------------------------|---------------------|
| L LENGTH            | 763 mm | L LENGTH            | 832 mm | WEIGHT EMPTY            | 9.4 Kg              |
| W WIDTH             | 399 mm | W WIDTH             | 466 mm | WEIGHT WITH FOAM        | 11.8 Kg             |
| D DEPTH             | 350 mm | D DEPTH             | 369 mm | WEIGHT WITH CUSTOM FOAM | Kg                  |
| LID                 | 50 mm  |                     |        | VOLUME                  | 106.6 lt            |
| BASE                | 300 mm |                     |        | BUOYANCY                | 82.2 Kg/max         |
|                     |        |                     |        | OPERATING TEMPERATURE   | °C min -33 / max 90 |

IMPERIAL IN-LBS-F°



| INTERNAL DIMENSIONS |             | EXTERNAL DIMENSIONS |           | OTHER DATA              |                |
|---------------------|-------------|---------------------|-----------|-------------------------|----------------|
| L LENGTH            | 30 1/16 in  | L LENGTH            | 32 3/4 in | WEIGHT EMPTY            | 20.72 lbs      |
| W WIDTH             | 15 11/16 in | W WIDTH             | 18 3/8 in | WEIGHT WITH FOAM        | 26.01 lbs      |
| D DEPTH             | 13 3/4 in   | D DEPTH             | 14 1/2 in | WEIGHT WITH CUSTOM FOAM | lbs            |
| LID                 | 1 15/16 in  |                     |           | VOLUME                  | 28.16 gal      |
| BASE                | 11 13/16 in |                     |           | BUOYANCY                | 181.22 lbs/max |

OPERATING  
TEMPERATURE

°F min -27.4 / max  
194